

Enable large-volume printing on a wide range of paper sizes—up to Ledger/A3—with a 4,600-sheet maximum input capacity.² Preview and edit scanning jobs. Centrally manage printing policies. Safeguard sensitive business information.

Print speed:13 Up to 40 ppm black (letter)

Print resolution: Up to 1200 x 1200 dpi black (best)

Scan resolution: Up to 600 x 600 dpi hardware, Up to 600 dpi Optical

Standard connectivity: 2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Foreign Interface; 1 Hardware Integration Pocket; 2 Internal USB Host

Duty cycle:14 Up to 200,000 pages

Duplex print options: Automatic (standard)

Mobile printing capability: HP ePrint, Apple AirPrint™



(HP LaserJet Enterprise MFP M725dn shown)



HP LaserJet Enterprise



HP LaserJet Enterprise



HP LaserJet Enterprise
MFP M725z+

Expand your options with sharp Ledger/A3 printing

- Empower your teams to do more—print, scan, copy, and fax¹ on paper sizes up to Ledger/A3—from a desktop-sized MFP.
- Stay focused on work—paper capacity up to 4,600 sheets and high-capacity cartridges limit interruptions.^{2,4}
- Get impressive document quality with near edge-to-edge printing and a convenient, built-in stapler.⁵
- Print what you need, even on the go—from your smartphone or tablet—using HP ePrint³ or Apple Airprint™.⁶

Quicken your business pace

- Streamline tasks—print, scan, copy, and fax¹ projects directly at the MFP's large color touchscreen.
- Save time by launching one-touch workflows with HP Quick Sets.
- Get just the results you need—using touchscreen controls to preview, edit, and reorder scans at the device.
- Easily send scanned files to a fax, folder, email, or USB.
 Print right from a memory device via the USB port.

Manage and protect your fleet for the long run

- Simplify fleet management using world-class tools such as HP Web Jetadmin,⁷ and reliably safeguard devices.
- Safeguard data—at rest or in transit—with an encrypted hard drive, user authentication, and security features.
- Add security tools—such as card and badge readers via the hardware integration pocket.⁸

• Extend the capabilities of workteam print environments, using a rich array of easy-to-integrate solutions.

Help save energy and reduce environmental impact

- Reduce energy use with HP Auto-On/Auto-Off Technology,⁹ and conserve power with Instant-on Technology.¹¹
- Use optional HP EcoSMART Fleet to easily create and manage environmental printing policies and practices.
- Conserve resources and save paper—use automatic two-sided printing.
- Easily recycle Original HP LaserJet toner cartridges through HP Planet Partners.¹²

HP EcoSolutions

- Reduce energy use with Instant-on Technology.¹
- Reduce paper use by up to 50%, using automatic two-sided printing.
- Reduce waste—scan, store, and distribute documents digitally.

Join HP in more sustainable printing hp.com/ecosolutions



¹ Compared with products that use traditional fusing

¹Fax capabilities are available with an optional fax card on the HP LaserJet Enterprise MFP M725dn. ² Maximum paper capacity of 4,600 sheets requires the purchase of optional paper tray accessories. ³ Requires an Internet connection to HP web-enabled printer and HP ePrint accounts registration (for a list of eligible printers, supported documents and image types and other HP ePrint details, see hpconnected.com). Mobile devices require Internet connection and email capability. May require wireless escess points. Separately purchased data plans or usage fees may apply. Print times and connection speeds may vary. Some HP LaserJet printers may require firmware upgrades. ⁴ High-capacity cartridges are optional for the HP LaserJet Enterprise 700 MFP Series M725. ⁵ In-line stapler is not available on the HP LaserJet Enterprise MFP M725dn or M725f. ⁵ Supports the following devices running iOS 4.2 or later: iPad® , iPad® 2, iPhone® (3GS or later), iPod touch® (3rd generation or later). Works with HP's Air Print-enabled printers and requires the printer be connected to the same network as your iOS device. Wireless performance is dependent upon physical environment and distance from the access point. Air Print, the Air Print Logo, iPad, iPhone, and iPod touch are trademarks of Apple® inc., registered in the U.S. and other countries. ¹ HP Web be letadmin is free and can be downloaded at hp.com/go/webjetadmin. ⁵ Solutions deployed through the hardware integration pocket may require additional purchase. ⁵ HP Auto-On/Auto-Onf Technology capabilities subject to printer and settings; may require additional purchase. ⁵ HP Auto-On/Auto-Onf Technology capabilities subject to printer and settings; may require additional purchase. ⁵ HP Auto-On/Auto-Onf Auto-Onf Auto-Onf Auto-Onf Auto-Onf Auto-Onf Technology capabilities varies. Original HP cartridge return and recycling is currently available in more than 50 countries, territories and regions in Asia, Europe, and North and South America through the HP Planer Partners program. For mo

HP LaserJet Enterprise MFP M725 series

- 1 100-sheet automatic document feeder
- 2 Intuitive 8-inch pivoting color touchscreen control panel with FutureSmart firmware and scan preview
- 3 Hardware integration pocket (HIP) for solution integration
- 4 Easy-access USB port to save and print files directly
- 5 In-line stapler with 500-sheet output bin
- 6 Built-in automatic two-sided printing
- 7 Two 250-sheet input trays, one supporting up to legal and one supporting up to ledger/A3
- 8 3,500-sheet high-capacity feeder and stand for a 4,100-sheet total input capacity
- 9 250-sheet output bin
- 10 Side door allows convenient access to the all-in-one HP print cartridge
- 11 100-sheet multipurpose tray 1 supports a wide variety of paper sizes and types
- 12 800 MHz processor, 1 GB standard memory
- 13 Two internal USB Host ports (for connecting third-party devices)
- 14 HP High-Performance Secure Hard Disk
- 15 Fax port
- 16 Foreign Interface port
- 17 HP Jetdirect Gigabit Ethernet print server
- 18 Hi-Speed USB 2.0 device port
- 19 Hi-Speed USB 2.0 Host port

HP LaserJet Enterprise MFP M725z+ printer shown



Series at a glance









	M725dn MFP	M725f MFP	M725z MFP	M725z+ MFP
Part number	CF066A	CF067A	CF068A	CF069A
Gigabit Ethernet networking				
Automatic two-sided printing				
100-sheet multipurpose tray 1				
2 x 250-sheet trays 2 and 3				
500-sheet tray¹	Optional		Not available	Optional
500-sheet feeder with cabinet and stand ¹	Optional		Not available	Not available
3 x 500-sheet feeder and stand¹	Optional	Not available		Not available
3,500-sheet high-capacity feeder and stand¹	Optional	Not available	Not available	
500-sheet in-line stapler	Not available	Not available		
HP High-Performance Secure Hard Disk				
Fax	Optional			
ENERGY STAR® qualified				

Top features

Get precise document finishing, one-touch workflows, and many scan-to options on a versatile Ledger/A3 MFP. Do more—with document sizes up to Ledger/A3, and high-capacity cartridges³ and paper trays. Print nearly to the page's edge, and even staple (Only on Z and Z+ models). Copy. scan. and fax1—and print from smartphones and tablets from virtually anywhere with HP ePrint.2

Set a swift pace—use this powerful MFP to keep your work moving. Save time and make your job easier, using HP Quick Sets. Preview and control jobs on the 8-inch color touchscreen. Scan to multiple locations, and print via an easy-access USB port.

Monitor your devices with industry-leading tools, including HP Web Jetadmin.4 Help protect data both in transit and at rest. Enhance security with PIN printing. Add safeguards via the hardware integration pocket. Integrate tomorrow's solutions with ease.

Help conserve resources and meet corporate environmental goals. HP Auto-On/Auto-Off Technology helps reduce energy use. 5 Easily manage printing policies with HP EcoSMART Fleet.⁶ Save paper, using automatic two-sided printing.

Get the most out of your printer with HP accessories, supplies, and services.

HP services

Downtime can have serious consequences, so HP provides support beyond the standard warranty. You benefit from reduced risk, maximized uptime, predictable service delivery and no unbudgeted repair costs. Choose from:

Optimized Care (optimum performance and stability):

4 hour Onsite Support, Maintenance Kit Replacement Service, Installation with Network Configuration Service

Standard Care (high level of uptime):

Next Business Day Onsite Support, Maintenance Kit Replacement Service, Installation with Network Configuration Service

Basic Care (minimum recommended support):

Next Business Day Onsite Support

4 hr Onsite Support: Onsite support within four hours after a service call received within the coverage window

Next Business Day Onsite Support: Onsite service the next business day after the service call is received

Maintenance Kit Replacement Service: Onsite replacement of your printer's maintenance kit including parts, materials, and labor

Installation with Network Configuration Service: Assembly, network configuration, and basic administrator familiarization

For more information about HP Care Pack, HP Contractual, or HP Managed Print Services, visit hp.com/go/printservices

Printers

HP LaserJet Enterprise 700 MFP M725dn	CF066A
HP LaserJet Enterprise 700 MFP M725f	CF067A
HP LaserJet Enterprise 700 MFP M725z	CF068A
HP LaserJet Enterprise 700 MFP M725z+	CF069A

Ink Cartridges

HP 14A Black LaserJet Toner Cartridge (10,000 pages)	CF214A
HP 14X Black LaserJet Toner Cartridge (17.500 pages)	CF214X

Accessories

500-sheet feeder and tray assembly	CF239A
1x500-sheet feeder, cabinet, and stand	CF243A
3x500-sheet feeder and stand	CF242A
3,500-sheet HCl and stand	CF245A
110v Maintenance/Fuser Kit	CF249A
220v Maintenance/Fuser Kit	CF254A
HP 200-pin DDR2 512MBx64 DIMM	CF306A
HP staple cartridge refill	C8091A
HP LaserJet MFP Analog Fax Accessory 500	CC487A
ADF Roller kit	L2718A

HP Care Pack	
HP 3-year Next Business Day + DMR LaserJet M725 MFP Support	U7A14E
HP 3-year 4h 9x5 LaserJet M725 MFP Hardware Support	U7A08E
HP 3-year 4h 13x5 LaserJet M725 MFP Hardware Support	U7A09E
HP 2-year Post Warranty Next Business Day LaserJet M725MFP	
Hardware Support	U7Y73PE
HP 1-year Post Warranty Next Business Day + DMR LaserJet M725 MFP Support	U7Y76PE

To know what HP Care Pack services exist for your product, please visit Care Pack Central at hp.com/go/cpc

Paper

hp.com/go/paper

Software

HP Web Jetadmin: hp.com/go/wja HP Universal Print Driver: hp.com/go/upd

¹ Fax capabilities are available with an optional fax card on the HP LaserJet Enterprise MFP M725dn. 2 Requires an Internet connection to HP web-enabled printer and HP ePrint account registration (for a list of eligible printers, supported documents and image types and other HP ePrint details, see hpconnected.com). Mobile devices require Internet connection and email capability. May require wireless access point. Separately purchased data plans or usage fees may apply. Print times and connection speeds may vary. Some HP LaserJet printers may require firmware upgrades. High-capacity cartridges are optional for the HP LaserJet Enterprise 700 MFP Series M725. 4 HP Web Jetadmin is free and can be downloaded at hp.com/go/webjetadmin. 5 HP Auto-On/Auto-Off Technology capabilities subject to printer and settings; may require a firmware upgrade, 6 HP EcoSMART Fleet must be purchased separately.

HP LaserJet Enterprise MFP M725 series

	HP LaserJet Enterprise 700 MFP M725dn (CF066A)	HP LaserJet Enterprise 700 MFP M725f (CF067A)	HP LaserJet Enterprise 700 MFP M725z (CF068A)	HP LaserJet Enterprise 700 MFP M725z+ (CF069A)
AIO functions	Print, copy, scan		Print, copy, scan, fax	, , , , , , , , , , , , , , , , , , , ,
Print				
Duplex print options		Automatio	c (standard)	
Print speed ¹		Up to 40 ppm (Black, letter); F	irst page out²: As fast as 10 sec	
Print technology		La	aser	
Print resolution	Black (best): Up to 12	00 x 1200 dpi; Black (normal): HP FastRes 1200 (12	200 dpi quality), 600 x 600 dpi with HP Resolu	tion Enhancement technology
Printer Smart Software	LID aDvint Apple Air	Print Open Futensibility Platform FutureSmart Fire	nuare LID Auto On/Auto Off technology Facu	Assass LICR Imped Provious
features	ne eeriiit, appte airi	Print, Open Extensibility Platform, FutureSmart Firn	nware, HP Auto-On/Auto-On technology, Easy	Access OSB, illiage Preview
Mobile printing capability		HP ePrint; A	Apple AirPrint	
Standard print languages		HP PCL 6; HP PCL 5e; HP pos	stscript level 3 emulation; PDF	
Scan				
Scan type/technology		Flatbed, ADF; Technology:	Charge Coupled Device (CCD)	
Scan speed ³		Letter: Up to 49 ppm (black a	and white), up to 30 ppm (color)	
Scan resolution		Hardware: Up to 600 x 60	0 dpi; Optical: Up to 600 dpi	
Scan file format		PDF, JPEG, TIFF,	MTIFF, XPS, PDF/A	
Scan input modes	Copy, scan to	e-mail, scan to network folder, scan to USB, save to	device memory, fax, Open Extensibility Platfo	orm (OXP) applications
Scan size maximum			17 in (297 x 420 mm)	
Scanner advanced features	Optimize text/picture; Image adjustments; .	Job build; Output quality setting; Selectable scan re		e erase; Auto tone; Auto job notification; Blank page
Bit depth/Grayscale levels			it/256	
iopy		ETO	11, 250	
Copy speed ⁴		Un to 40 com	n (Black, letter)	
Copy resolution			phics): 600 x 600 dpi	
Max number of copies			999 copies	
Copier reduce/enlarge	1		999 copies 0 400%	
Copier reduce/entarge Copier settings	Sides: Collate: Dance Colection: D. dura	25 to Enlarge; Image Adjustment; Content Orientation; P/		Ontimize Text/Dictures Original Ciaes Joh Build
	Sides, Collate, Paper Selection, Reduce	/Enlarge, image Adjustment, content orientation, P	ages per sneet, booklet format, Euge to Euge	; Optimize Text/Picture; Original Size; Job Build
Digital Sending Standard features	Scan to e-mail; Save-	to-Network Folder; Save-to-USB drive; Send to FTP;	; Send to LAN Fax; Send to Internet Fax; Local	Address Book; SMTP over SSL
ax	<u> </u>			
	Not Applicable		Up to 22 6 kbps, 2 ses per page	
Transmission speed⁵	Not Applicable	PII-/I	Up to 33.6 kbps; 3 sec per page	: 204 x 98 dpi; Black and White (fine): 204 x 196 dpi,
Fax resolution	Not Applicable		ack Photo Grayscale: 300 x 300 dpi (400 x 40	
Fax smart software features	Not Applicable	Stored faxes; fax archiving; fax forwarding		fax; fax number confirmation; Holiday fax schedule
			Up to 100 pages	
Fax memory	Not Applicable	Auto Fay Peduction Supported: Voc: Auto-Pe	dialing: Voc. Eav Delayed Sending: No. Dictin	sctive Ping Retection Supported: No: Fay Forwardin
Fax features	Not Applicable	Supported: Yes; Fax Phone TAM Interface Suppo	orted: No; Fax Polling Supported: Yes (poll to	receive only); Junk Barrier Supported: Yes; PC Inter
Fax features		Supported: Yes; Fax Phone TAM Interface Suppo		receive only); Junk Barrier Supported: Yes; PC Inter
Fax features	Not Applicable	Supported: Yes; Fax Phone TAM Interface Supported: Yes; To	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telep	receive only); Junk Barrier Supported: Yes; PC Inter hone Mode Supported: No
Fax features	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S	Supported: Yes; Fax Phone TAM Interface Supported: Yes; To Supported: Yes; To Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 00T network; 1 Foreign Interface; 1 Hardware	receive only); Junk Barrier Supported: Yes; PC Inter hone Mode Supported: No Integration Pocket; 2 Internal USB Host
Fax features	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Tu Supported: Yes; Tu Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 er (standard) supports: 10Base-T, 100Base-Tx, 1000	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 100T network; 1 Foreign Interface; 1 Hardware 18ase-T; 802.3az (EEE) support on Fast Ethern	receive only); Junk Barrier Supported: Yes; PC Inter hone Mode Supported: No Integration Pocket; 2 Internal USB Host
Fax features Connectivity Standard connectivity Network capabilities	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Tu Supported: Yes; Tu Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 er (standard) supports: 10Base-T, 100Base-Tx, 1000 networkir	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 00T network; 1 Foreign Interface; 1 Hardware 18ase-T; 802.3az (EEE) support on Fast Ethern ng (optional)	receive only); Junk Barrier Supported: Yes; PC Inter hone Mode Supported: No Integration Pocket; 2 Internal USB Host
Fax features Connectivity Standard connectivity Network capabilities Wireless capability	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Tu Supported: Yes; Tu Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 er (standard) supports: 10Base-T, 100Base-Tx, 1000 networkir	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 100T network; 1 Foreign Interface; 1 Hardware 18ase-T; 802.3az (EEE) support on Fast Ethern 19 (optional) chase of a hardware accessory	receive only); Junk Barrier Supported: Yes; PC Inter hone Mode Supported: No Integration Pocket; 2 Internal USB Host
Fax features Connectivity Standard connectivity Network capabilities Wireless capability Modem	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S	Supported: Yes; Fax Phone TAM Interface Supported: Yes; To Supported: Yes; To Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 er (standard) supports: 10Base-T, 100Base-Tx, 1000 networkir Optional, enabled with purc	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 100T network; 1 Foreign Interface; 1 Hardware IBase-T; 802.3az (EEE) support on Fast Ethern 12 (optional) 12 chase of a hardware accessory 33.6 kbps	receive only); Junk Barrier Supported: Yes; PC Interl hone Mode Supported: No Integration Pocket; 2 Internal USB Host
Fax features Connectivity Standard connectivity Network capabilities Wireless capability Modem Memory	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Tu Supported: Yes; Tu Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 er (standard) supports: 10Base-T, 100Base-Tx, 1000 networkir Optional, enabled with purc	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 100T network; 1 Foreign Interface; 1 Hardware 18ase-T; 802.3az (EEE) support on Fast Ethern 10 (optional) 1. chase of a hardware accessory 33.6 kbps 1 GB	
Fax features Connectivity Standard connectivity Network capabilities Wireless capability Modern Memory Processor speed	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Ti Supported: Yes; Ti Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 er (standard) supports: 10Base-T, 100Base-Tx, 1000 networkin Optional, enabled with purc	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 000T network; 1 Foreign Interface; 1 Hardware Base-T; 802.3az (EEE) support on Fast Ethern (p (optional) chase of a hardware accessory 33.6 kbps GB D MHz	receive only); Junk Barrier Supported: Yes; PC Interl hone Mode Supported: No Integration Pocket; 2 Internal USB Host
Fax features Connectivity Standard connectivity Network capabilities Wireless capability Modem Memory Processor speed Duty cycle (monthly, A4) ⁶	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Ti Supported: Yes; Ti Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 er (standard) supports: 10Base-T, 100Base-Tx, 1000 networkin Optional, enabled with purc 1 800 Up to 200	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 100T network; 1 Foreign Interface; 1 Hardware 18ase-F; 802.3az (EEE) support on Fast Ethern 10 (optional) 1 chase of a hardware accessory 1 33.6 kbps 1 6 B 1 0 MHz 1 0,000 pages	receive only); Junk Barrier Supported: Yes; PC Inter hone Mode Supported: No Integration Pocket; 2 Internal USB Host
Fax features Connectivity Standard connectivity Network capabilities Wireless capability Modern Memory Processor speed Duty cycle (monthly, A4) ⁶ Recom monthly page volume ²	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Ti Supported: Yes; Ti Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 er (standard) supports: 10Base-T, 100Base-Tx, 1000 networkin Optional, enabled with purc 1 800 Up to 200	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 000T network; 1 Foreign Interface; 1 Hardware Base-T; 802.3az (EEE) support on Fast Ethern (p (optional) chase of a hardware accessory 33.6 kbps GB D MHz	receive only); Junk Barrier Supported: Yes; PC Inter hone Mode Supported: No Integration Pocket; 2 Internal USB Host
Fax features Connectivity Standard connectivity Network capabilities Wireless capability Modern Memory Processor speed Duty cycle (monthly, A4) ⁶ Recom monthly page volume ²	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Tri Supported: Yes; Tri Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 er (standard) supports: 10Base-T, 100Base-Tx, 1000 networkin Optional, enabled with purc	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 000T network; 1 Foreign Interface; 1 Hardware 18ase-T; 802.3az (EEE) support on Fast Ethern 19 (optional) chase of a hardware accessory 33.6 kbps GB 0 MHz 0,000 pages o 20,000 pages	receive only); Junk Barrier Supported: Yes; PC Interhone Mode Supported: No Integration Pocket; 2 Internal USB Host et and Gig Links; IPsec (standard); 802.11b/g/n wirele
Fax features Connectivity Standard connectivity Network capabilities Wireless capability Modern Memory Processor speed Duty cycle (monthly, A4) ⁶ Recom monthly page volume ²	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Ti Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 er (standard) supports: 10Base-T, 100Base-Tx, 100Bas	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 100T network; 1 Foreign Interface; 1 Hardware 1032-7; 802.3az (EEE) support on Fast Ethern 1032 (potional) 1033 chase of a hardware accessory 1045 and 1045 chase of a hardware accessory 1056 and 1057 chase of a hardware accessory 1057 chase of a hardware accessory 1058 chase of a hardware accessory 1058 chase of a hardware accessory 1058 chase of a hardware accessory 1059 chase of a hardware accessory 1050 chase of a hardware ac	receive only); Junk Barrier Supported: Yes; PC Inter hone Mode Supported: No Integration Pocket; 2 Internal USB Host et and Gig Links; IPsec (standard); 802.11b/g/n wireld
Fax features Connectivity Standard connectivity Network capabilities Wireless capability Modem Memory Processor speed Outy cycle (monthly, A4) ⁵ Recom monthly page volume ⁷ Paper handing	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Ti Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 er (standard) supports: 10Base-T, 100Base-Tx, 100Bas	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 000T network; 1 Foreign Interface; 1 Hardware 18ase-T; 802.3az (EEE) support on Fast Ethern 19 (optional) chase of a hardware accessory 33.6 kbps GB 0 MHz 0,000 pages o 20,000 pages	receive only); Junk Barrier Supported: Yes; PC Inter hone Mode Supported: No Integration Pocket; 2 Internal USB Host et and Gig Links; IPsec (standard); 802.11b/g/n wireld
Fax features Connectivity Standard connectivity Network capabilities Wireless capability Modem Memory Processor speed Outry cycle (monthly, A4) ⁶ Recom monthly page volume ⁷ Paper handing Media type Media weight Custom media sizes	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Ti Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 er (standard) supports: 10Base-T, 100Base-Tx, 1000 networkir Optional, enabled with purc 1 800 Up to 200 Up to 5000 t Up to 5000 t Tray 1: 16 to 53 lb (60 to 199 g/m²); Tray 1: 3 x 5 to 12.3 x 18.5 in; Tray 2: 5.8 x 8.3 t	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 100T network; 1 Foreign Interface; 1 Hardware 18ase-T; 802.3az (EEE) support on Fast Ethern 10 (optional) 10 chase of a hardware accessory 10	receive only); Junk Barrier Supported: Yes; PC Interhone Mode Supported: No Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele
Fax features Connectivity Standard connectivity Network capabilities Wireless capability Modem Memory Processor speed Duty cycle (monthly, A4) ⁶ Recom monthly page volume ⁷ Paper handing Media type Media type Media weight	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Ti Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 er (standard) supports: 10Base-T, 100Base-Tx, 1000 networkir Optional, enabled with purc 1 800 Up to 200 Up to 5000 t Up to 5000 t Tray 1: 16 to 53 lb (60 to 199 g/m²); Tray 1: 3 x 5 to 12.3 x 18.5 in; Tray 2: 5.8 x 8.3 t	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 100T network; 1 Foreign Interface; 1 Hardware 18ase; 7; 802.3az (EEE) support on Fast Ethern 19 (optional) 1 chase of a hardware accessory 1 33.6 kbps 1 MHz 1 0,000 pages 2 0,000 pages 2 0,000 pages 3 1 (ardstock, envelope Trays 2-6: 16 to 32 lb (60 to 120 g/m²)	receive only); Junk Barrier Supported: Yes; PC Interhone Mode Supported: No Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele
Fax features Connectivity Standard connectivity Network capabilities Wireless capability Modem Memory Processor speed Outy cycle (monthly, A4) ⁶ Recom monthly page volume ⁷ Paper handing Media type Media weight Custom media sizes ADF capacity	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Ti Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 er (standard) supports: 10Base-T, 100Base-Tx, 1000 networkir Optional, enabled with purc 1 800 Up to 200 Up to 5000 t Up to 5000 t Tray 1: 16 to 53 lb (60 to 199 g/m²); Tray 1: 3 x 5 to 12.3 x 18.5 in; Tray 2: 5.8 x 8.3 t	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 100T network; 1 Foreign Interface; 1 Hardware 18ase-F; 802.3az (EEE) support on Fast Ethern 10 (optional) 1 chase of a hardware accessory 1 chase of a hardware accessory 1 chase of a hardware accessory 2 chase of a hardware accessory 3 chase of a hardware accessory 2 chase of a hardware accessory 3 chase of a hardware acce	receive only); Junk Barrier Supported: Yes; PC Interhone Mode Supported: No Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele and Links; IPsec (standard); 802.11b/g/n wirele by Jabels, transparency, vellum 17 in 6.9 in (745 x 681 x 1192 mm);
Fax features Connectivity Standard connectivity Network capabilities Wireless capability Modem Memory Processor speed Outy cycle (monthly, A4) ⁶ Neterom monthly page volume ⁷ Paper handing Media type Media weight Custom media sizes ADF capacity	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable Paper (color, letterhe	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Ti Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 er (standard) supports: 10Base-T, 100Base-Tx, 100Ba	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 100T network; 1 Foreign Interface; 1 Hardware Baseer; 802.3az (EEE) support on Fast Ethern (optional) 1 chase of a hardware accessory 1 33.6 kbps 1 db MHz 1,000 pages 1 o 20,000 pages 1 o 20,000 pages 1 o 20,000 pages 1 o 21,000 pages 2 o 20,000 pages 2 o 20,000 pages 3 o 20,000 pages 3 o 20,000 pages 4 o 20,000 pages 5 o 20,000 pages 6 o 20,000 pages 7 o 21,7 x 14.3 in; Trays 3-6: 5.8 x 8.3 to 11.7 x 100 sheets 7 o 29.3 x 26.8 x 4 8 o 20,1 x 40.6 s	receive only); Junk Barrier Supported: Yes; PC Interhone Mode Supported: No Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integration Pocket; 3 Integration (standard); 802.11b/g/n wirele Integration Pocket; 4 Integration (standard); 802.11b/g/n wirele
Fax features Connectivity Standard connectivity Network capabilities Wireless capability Modem Memory Processor speed Outy cycle (monthly, A4) ⁶ Neteom monthly page volume ⁷ Paper handing Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H)	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable Paper (color, letterhe	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Ti Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 er (standard) supports: 10Base-T, 100Base-Tx, 100Bas	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 100T network; 1 Foreign Interface; 1 Hardware 18ase-F; 802.3az (EEE) support on Fast Ethern 10 (optional) 1 chase of a hardware accessory 1 chase of a hardware accessory 1 chase of a hardware accessory 2 chase of a hardware accessory 3 chase of a hardware accessory 2 chase of a hardware accessory 3 chase of a hardware acce	receive only); Junk Barrier Supported: Yes; PC Interhone Mode Supported: No Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele and Links; IPsec (standard); 802.11b/g/n wirele b, labels, transparency, vellum 17 in 6.9 in (745 × 681 × 1192 mm);
Fax features connectivity Standard connectivity Network capabilities Wireless capability Modern Nemory Processor speed Outry cycle (monthly, A4) ⁶ Neterom monthly page volume ⁷ Paper handing Media type Media weight Custom media sizes ADF capacity Volumensions (W x D x H) Veight	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable Paper (color, letterhe 24.2 × 25.6 × 24 in (614 × 649 × 609 mm) Max: 34.1 × 38.9 × 24 in (865 × 989 × 609 mm) 119.3 lb (54.11 kg)	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Ti Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 er (standard) supports: 10Base-T, 100Base-Tx, 100Bas	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 100T network; 1 Foreign Interface; 1 Hardware 18ase-F; 802.3az (EEE) support on Fast Ethern 10 (optional) 1 chase of a hardware accessory 1 dB 33.6 kbps 1 dB 0 MHz 1 dB 0 0000 pages 1 dB 0 0 0000 pages 1 dB 0 0 0000 pages 1 dB 0 0000 pages 1 dB 0 0 0000 pages 1 dB 0 0 0000 pages 1 dB 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	receive only); Junk Barrier Supported: Yes; PC Interhone Mode Supported: No Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele It is a supported in the support of the su
Fax features connectivity Standard connectivity Network capabilities Wireless capability Modern Nemory Processor speed Outry cycle (monthly, A4) ⁶ Neterom monthly page volume ⁷ Paper handing Media type Media weight Custom media sizes ADF capacity Volumensions (W x D x H) Veight	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable Paper (color, letterhe 24.2 × 25.6 × 24 in (614 × 649 × 609 mm) Max: 34.1 × 38.9 × 24 in (865 × 989 × 609 mm) 119.3 lb (54.11 kg)	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Ti Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 er (standard) supports: 10Base-T, 100Base-Tx, 100Bas	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 00T network; 1 Foreign Interface; 1 Hardware Base-T; 802.3az (EEE) support on Fast Ethern g (optional) chase of a hardware accessory 33.6 kbps 68 0 MHz 0,000 pages 0 20,000 pages 0 20,000 pages supph, tough paper), bond, cardstock, envelope Trays 2-6: 16 to 32 lb (60 to 120 g/m²) 0 11,7 x14.3 in; Trays 3-6: 5.8 x 8.3 to 11.7 x 100 sheets 29.3 x 26.8 x 4 Max: 36.1 x 40.6 x 206.3 lb (92.35 kg)	receive only); Junk Barrier Supported: Yes; PC Interhone Mode Supported: No Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele It is a supported in the support of the su
Fax features Connectivity Standard connectivity Network capabilities Wireless capability Modern Memory Processor speed Outy cycle (monthly, A4) ⁶ Necom monthly page volume ⁹ Paper handing Media type Media type Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the box ⁶	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable Paper (color, letterhe 24.2 × 25.6 × 24 in (614 × 649 × 609 mm) Max: 34.1 × 38.9 × 24 in (865 × 989 × 609 mm) 119.3 lb (54.11 kg)	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Ti Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 er (standard) supports: 10Base-T, 100Base-Tx, 100Bas	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 100T network; 1 Foreign Interface; 1 Hardware 18ase-F; 802.3az (EEE) support on Fast Ethern 10 (optional) 1 chase of a hardware accessory 1 dB 33.6 kbps 1 dB 0 MHz 1 dB 0 0000 pages 1 dB 0 0 0000 pages 1 dB 0 0 0000 pages 1 dB 0 0000 pages 1 dB 0 0 0000 pages 1 dB 0 0 0000 pages 1 dB 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	receive only); Junk Barrier Supported: Yes; PC Interhone Mode Supported: No Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele It is a supported in the support of the su
Fax features Connectivity Standard connectivity Network capabilities Wireless capability Modern Memory Processor speed Duty cycle (monthly, A4) ⁶ Necom monthly page volume' Paper handing Media type Media type Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the box ⁶ Warranty features	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable Paper (color, letterhe 24.2 x 25.6 x 24 in (614 x 649 x 609 mm) Max: 34.1 x 36.9 x 24 in (865 x 989 x 609 mm) 119.3 lb (54.11 kg) M725dn: HP Laser Jet Enterprise MFP M725; Windows 8, Windows 7, Windows Vista, Windo	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Ti Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 er (standard) supports: 10Base-T, 100Base-Tx, 100Bas	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 100T network; 1 Foreign Interface; 1 Hardware 18ase-T; 802.3az (EEE) support on Fast Ethern 10 (optional) 1 chase of a hardware accessory 1 degree 33.6 kbps 1 dB 2 db MHz 2 db MHz 2 db MHz 2 db MHz 3 db MHz 4 db MHz 5 db MHz 6 db MHz 6 db MHz 7 db MHz 7 db MHz 7 db MHz 7 db MHz 8 d	receive only); Junk Barrier Supported: Yes; PC Interhone Mode Supported: No Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integration Pocket; 2 Integrated Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integration Pocket; 2 Integrated Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integration Pocket; 2 Integrated Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integration Pocket; 2 Integrated Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integration Pocket; 2 Integrated Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integration Pocket; 2 Integrated Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integration Pocket; 2 Integrated Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integrated Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integrated Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integrated Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integrated Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integrated Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integrated Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integrated Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integrated Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integrated Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integrated Host let and Gig Links; 802.11b/g/n wirele Integrated Host let and Gi
Fax features Connectivity Standard connectivity Network capabilities Wireless capability Modem Memory Processor speed Duty cycle (monthly, A4) ⁵ Recom monthly page volume ⁷ Paper handing Media type Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the box ⁴ Warranty features Compatible operating	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable Paper (color, letterhe 24.2 x 25.6 x 24 in (614 x 649 x 609 mm) Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm) 119.3 lb (54.11 kg) M725dn: HP LaserJet Enterprise MFP M725; Windows 8, Windows 7, Windows Vista, Windou 10.6, 05 X Lion, 05 X Mountain Lion; For the lates	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Ti Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 er (standard) supports: 10Base-T, 100Base-Tx, 100Bas	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 100T network; 1 Foreign Interface; 1 Hardware 18ase-T; 802.3az (EEE) support on Fast Ethern (g (optional) hase of a hardware accessory 33.6 kbps 6B 0 MHz 0,000 pages 0 20,000 pages 0 20,000 pages 0 ugh, tough paper), bond, cardstock, envelope 17ays 2-6: 16 to 32 lb (60 to 120 g/m²) 0 11.7 x 14.3 in; 17ays 3-6: 5.8 x 8.3 to 11.7 x 100 sheets 29.3 x 26.8 x 4 Max: 36.1 x 40.6 x 206.3 lb (92.35 kg) lardware Installation Guide, Support flyer, Wal 1725z+: Same as above plus Telecom cable 1-site warranty 208 (32 and 64-bit), Windows Server 26 erminal Services (hp.com/go/upd); Novell (nove	receive only); Junk Barrier Supported: Yes; PC Interhone Mode Supported: No Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele In the land Gig Links; 802.11b/g/n wirele In the lan
Fax features Connectivity Standard connectivity Network capabilities Wireless capability Modem Memory Processor speed Outy cycle (monthly, A4) ⁵ Recom monthly page volume ⁷ Paper handing Media type Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the box ⁸ Warranty features Compatible operating	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable Paper (color, letterhe Paper (color, letterhe 24.2 × 25.6 × 24 in (614 × 649 × 609 mm) Max: 34.1 × 38.9 × 24 in (865 × 989 × 609 mm) 119.3 lb (54.11 kg) M725dn: HP LaserJet Enterprise MFP M725; Windows 8, Windows 7, Windows Vista, Windol 10.6, 0S X Lion, 0S X Mountain Lion; For the late hp.com/go/unixmodelscripts, hp.com/go/	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Ti Supported:	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 00T network; 1 Foreign Interface; 1 Hardware Base-T; 802.3az (EEE) support on Fast Ethern go (potional) chase of a hardware accessory 33.6 kbps 6B 0 MHz 0,000 pages 0 20,000 pages 0 20,000 pages outh, tough paper), bond, cardstock, envelope Trays 2-6: 16 to 32 lb (60 to 120 g/m²) 0 11.7 x 14.3 in; Trays 3-6: 5.8 x 8.3 to 11.7 x 100 sheets 29.3 x 26.8 x 4 Max: 36.1 x 40.6 x 206.3 lb (92.35 kg) lardware Installation Guide, Support flyer, Wal 1725z+; Same as above plus Telecom cable -site warranty Server 2008 (32 and 64-bit), Windows Server 20 (go/sap/drivers, hp.com/go/pap/print); HP e	receive only); Junk Barrier Supported: Yes; PC Inter hone Mode Supported: No Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirelet and Gig Links; 802.
Fax features connectivity Standard connectivity Network capabilities Wireless capability Modern Memory Processor speed Outy cycle (monthly, A4) ⁶ Neterom monthly page volume ⁷ Paper handing Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Veight What's in the box ⁸ Varranty features compatible operating ystems	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable Paper (color, letterhe Paper (color, letterhe 24.2 × 25.6 × 24 in (614 × 649 × 609 mm) Max: 34.1 × 38.9 × 24 in (865 × 989 × 609 mm) 119.3 lb (54.11 kg) M725dn: HP LaserJet Enterprise MFP M725; Windows 8, Windows 7, Windows Vista, Windol 10.6, 0S X Lion, 0S X Mountain Lion; For the late hp.com/go/unixmodelscripts, hp.com/go/	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Ti Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 er (standard) supports: 10Base-T, 100Base-Tx, 1000 er (standard) supports: 10Base-T, 100Base-Tx, 1000 networkin Optional, enabled with purc 11 800 Up to 200 Up to 5000 to Up to 5000 to Tray 1: 16 to 53 lb (60 to 199 g/m²); Tray 1: 3 x 5 to 12.3 x 18.5 in; Tray 2: 5.8 x 8.3 to Standard, 29.3 x 26.8 x 45.7 in (745 x 681 x 1160 mm); Max: 36.1 x 40.6 x 45.7 in (917 x 1032 x 1160 mm) 192.3 lb (87.1 kg) HP Black LaserJet Toner Cartridge (10,000 pages); F CD-ROM; Power cord. M725f, M725z & M One-year on ws XP (SP2+), Windows Server 2003 (SP1+), Windows St operating system support see: Citrix and Windows Teddirectunix_software); SAP device types (hp.com, lows XP (SP2+), Windows Server 2003 (SP1+), Windows Win	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 100T network; 1 Foreign Interface; 1 Hardware 18ase-T; 802.3az (EEE) support on Fast Ethern 10 (potpional) 1 chase of a hardware accessory 1 33.6 kbps 1 MHz 1 0,000 pages 1 0 20,000 pages 2 02,000 pages 2 02,000 pages 2 02,000 pages 2 04,000 pages 2 05,000 pages 3 1 0 1.7 x 14.3 in; Trays 3-6: 5.8 x 8.3 to 11.7 x 1 100 sheets 2 03.3 k 26.8 x 4 2 04.3 k 3 1 x 40.6 y 2 05.3 b [92.35 kg] 1 4ardware Installation Guide, Support flyer, Waltz-Steve Same as above plus Telecom cable 1 period of the side of t	In receive only); Junk Barrier Supported: Yes; PC Interhone Mode Supported: No Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wireli Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wireli It is a links; IPsec (s
Fax features Connectivity Standard connectivity Network capabilities Wireless capability Modem Memory Processor speed Outy cycle (monthly, A4) ⁶ Necom monthly page volume ⁷ Paper handing Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the box ⁶ Warranty features Compatible operating systems Alnimum system	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable Paper (color, letterhe 24.2 x 25.6 x 24 in (614 x 649 x 609 mm) Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm) 119.3 lb (54.11 kg) M725dn: HP LaserJet Enterprise MFP M725; Windows 8, Windows 7, Windows Vista, Windo 10.6, 05 X Lion, 05 X Mountain Lion; For the lates hp.com/go/unixmodelscripts, hp.com/go/j PC: Windows 8, Windows 7, Windows Vista, Windo	Supported: Yes; Fax Phone TAM Interface Supposed: Yes; Ti Supported: Yes; Ti Optional, enabled with purc 1 800 Up to 200 Up to 5000 to Up to 5000 to Up to 5000 to Tray 1: 16 to 53 lb (60 to 199 g/m²); Tray 1: 3 x 5 to 12.3 x 18.5 in; Tray 2: 5.8 x 8.3 ti Standard, 29.3 x 26.8 x 45.7 in (745 x 681 x 1160 mm); Max: 36.1 x 40.6 x 45.7 in (917 x 1032 x 1160 mm) 192.3 lb (87.1 kg) HP Black LaserJet Toner Cartridge (10,000 pages); H CROM; Power cord. M725f, M725z & M One-year on ws XP (SP2+), Windows Server 2003 (SP1+), Windows st operating system support see: Citrix and Windows Teddirectunix_software); SAP device types (hp.com, lows XP (SP2+), Windows Server 2003 (SP1+), Windows Space; operating system compatible hardws	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 000T network; 1 Foreign Interface; 1 Hardware Base-T; 802.3az (EEE) support on Fast Ethern (p (optional) chase of a hardware accessory 33.6 kbps 68 0 MHz 0,000 pages 0 20,000 pages 0 20,	preceive only); Junk Barrier Supported: Yes; PC Interhone Mode Supported: No Integration Pocket; 2 Internal USB Host et and Gig Links; IPsec (standard); 802.11b/g/n wirele p. Labels, transparency, vellum 17 in 6.9 in (745 x 681 x 1192 mm); x 46.9 in (745 x 681 x 1192 mm) 225.8 lb (102.42 kg) 17 rranty guide; Printer documentation and software on 18 R2 (64-bit), Windows Server 2012 (64-bit); Mac OS X 18 ell.com/iprint); Linux (hplip.net); UNIX (hp.com/go/unix) 19 Print Mobile Driver (hp.com/go/eprintmobiledriver) 19 int Mobile Driver (hp.com/go/eprintmobiledriver) 10 integration of the com/go/eprintmobiledriver) 10 integration of the com/go/eprintmobiledriver)
Fax features Connectivity Standard connectivity Network capabilities Wireless capability Moder Memory Processor speed Outy cycle (monthly, A4) ⁵ Recom monthly page volume ⁷ Paper handing Media type Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the box ⁶ Warranty features Compatible operating systems Minimum system	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable Paper (color, letterhe Paper (color, letterhe 24.2 × 25.6 × 24 in (614 × 649 × 609 mm) Max: 34.1 × 38.9 × 24 in (865 × 989 × 609 mm) 119.3 lb (54.11 kg) M725dn: HP Laser Jet Enterprise MFP M725; Windows 8, Windows 7, Windows Vista, Windolos 10.6, OS X Lion, OS X Mountain Lion; For the lates hp.com/go/unixmodelscripts, hp.com/go/j PC: Windows 8, Windows 7, Windows Vista, Windows Vista, Windows 7, Windows Vista, Windows 7, Windows Vista, Windows 7, Windows Vista, Windows 7, Windows Vista, Windows Vista, Windows 7, Windows Vista,	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Ti Supported:	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 00T network; 1 Foreign Interface; 1 Hardware Base-T; 802.3az (EEE) support on Fast Ethern go (potional) chase of a hardware accessory 33.6 kbps 6B 0 MHz 0,000 pages 0 20,000 pages o 20,000 pages outh, tough paper), bond, cardstock, envelope Trays 2-6: 16 to 32 lb (60 to 120 g/m²) 0 11.7 x 14.3 in; Trays 3-6: 5.8 x 8.3 to 11.7 x 100 sheets 29.3 x 26.8 x 4 Max: 36.1 x 40.6 x 206.3 lb (92.35 kg) lardware Installation Guide, Support flyer, Wal 1725z+; Same as above plus Telecom cablesite warranty Server 2008 (32 and 64-bit), Windows Server 20 grafsap/drivers, hp.com/go/pap/print); HP e ows Server 2008, Windows Server 208 R2, Ware system requirements, see microsoft.com ystem compatible hardware system requirements	receive only); Junk Barrier Supported: Yes; PC Interhone Mode Supported: No Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele It is a supported by the support of the supported by the support of the support
Fax features Connectivity Standard connectivity Network capabilities Wireless capability Modem Memory Processor speed Outy cycle (monthly, A4) ⁶ Necom monthly page volume ⁷ Paper handing Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the box ⁶ Warranty features Compatible operating systems Winimum system requirements	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable Paper (color, letterhe 24.2 x 25.6 x 24 in (614 x 649 x 609 mm) Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm) 119.3 lb (54.11 kg) M725dn: HP Laser Jet Enterprise MFP M725; Windows 8, Windows 7, Windows Vista, Windo 10.6, 0S X Lion, 0S X Mountain Lion; For the later hp.com/go/unixmodelscripts, hp.com/go/j PC: Windows 8, Windows 7, Windows Vista, Windows Vista, Windows 7, Windows Vista, Windows 105 internal TrueType fonts scalable in HP PCL, 105 inter	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Ti Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10 er (standard) supports: 10Base-T, 100Base-Tx, 1000 er (standard) supports: 10Base-T, 100Base-Tx, 1000 networkin Optional, enabled with purc 11 800 Up to 200 Up to 5000 to Up to 5000 to Tray 1: 16 to 53 lb (60 to 199 g/m²); Tray 1: 3 x 5 to 12.3 x 18.5 in; Tray 2: 5.8 x 8.3 to Standard, 29.3 x 26.8 x 45.7 in (745 x 681 x 1160 mm); Max: 36.1 x 40.6 x 45.7 in (917 x 1032 x 1160 mm) 192.3 lb (87.1 kg) HP Black LaserJet Toner Cartridge (10,000 pages); P CD-ROM; Power cord. M725f, M725z & M One-year on ws XP (SP2+), Windows Server 2003 (SP1+), Windows St operating system support see: Citrix and Windows. Te tedirectunix_software); SAP device types (hp.com, lows XP (SP2+), Windows Server 2003 (SP1+), Windows Te space; operating system compatible hardwain Lion; 1 GB available hard disk space; operating sy	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 100T network; 1 Foreign Interface; 1 Hardware 18ase-T; 802.3az (EEE) support on Fast Ethern 19 (optional) 1 chase of a hardware accessory 1 degree of the Support on Fast Ethern 19 (optional) 2 degree of the Support on Fast Ethern 19 (optional) 3 degree of the Support on Fast Ethern 19 (optional) 3 degree of the Support on Fast Ethern 19 (optional) 4 degree of the Support 19 (optional) 5 degree of the Support 19 (optional) 6 degree of the Support 19 (optional) 6 degree of the Support 19 (optional) 7 degree of the Support 19 (optional) 8 degree of the Support 19 (optional) 9 degree o	In receive only); Junk Barrier Supported: Yes; PC Interhone Mode Supported: No Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integration Pocket; 2 Internal Wind Integration Pocket; 2 Integration Pock
Fax features Connectivity Standard connectivity Network capabilities Wireless capability Modem Memory Processor speed Outy cycle (monthly, A4) ⁶ Netecom monthly page volume ⁷ Paper handing Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the box ⁶ Warranty features Compatible operating systems Winimum system equirements Control of the control	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable Paper (color, letterhe Paper (color, letterhe 24.2 x 25.6 x 24 in (614 x 649 x 609 mm) Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm) 119.3 lb (54.11 kg) M725dn: HP LaserJet Enterprise MFP M725; Windows 8, Windows 7, Windows Vista, Windo 10.6, 05 X Lion, 05 X Mountain Lion; For the lates hp.com/go/unixmodelscripts, hp.com/go/j PC: Windows 8, Windows 7, Windows Vista, Windo Mac: Mac OS X 10.6, 05 X Lion, 05 X Mount. 105 internal TrueType fonts scalable in HP PCL, 5 Vista 8 Fonts (Calibri, Cambria); addit	Supported: Yes; Fax Phone TAM Interface Suppose Supported: Yes; Ti Supported: Yes; Tray 1: 16 to 53 lb (60 to 199 g/m²); Tray 1: 3 x 5 to 12.3 x 18.5 in; Tray 2: 5.8 x 8.3 to Supported: Yes; Tray 1: 3 x 5 to 12.3 x 18.5 in; Tray 2: 5.8 x 8.3 to Supported: Yes; Tray 1: 3 x 5 to 12.3 x 18.5 in; Tray 2: 5.8 x 8.3 to Supported: Yes; Yes; Yes; Yes; Yes; Yes; Yes; Yes;	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi (2007 network; 1 Foreign Interface; 1 Hardware Base-T; 802.3az (EEE) support on Fast Ethern (9 (optional) chase of a hardware accessory 33.6 kbps (68 0 MHz),000 pages 0 20,000 pages 0 2	preceive only); Junk Barrier Supported: Yes; PC Interhone Mode Supported: No Integration Pocket; 2 Internal USB Host et and Gig Links; IPsec (standard); 802.11b/g/n wirele processes to the second of the second o
Fax features Connectivity Standard connectivity Network capabilities Wireless capability Modern Modern Memory Processor speed Outy cycle (monthly, A4)'s Recom monthly page volume' Paper handing Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the box's Warranty features Compatible operating systems Minimum system equirements Control panel	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable Paper (color, letterhe Paper (color, letterhe 24.2 x 25.6 x 24 in (614 x 649 x 609 mm) Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm) 119.3 lb (54.11 kg) M725dn: HP Laser Jet Enterprise MFP M725; Windows 8, Windows 7, Windows Vista, Windo 10.6, 05 X Lion, 05 X Mountain Lion; For the lates hp.com/go/unixmodelscripts, hp.com/go/Jet. Windows 7, Windows Vista, Windows 7, Windows Vista, Windows 7, Windows Vista, Windows 7, Windows Vista, Windows 105 internal TrueType fonts scalable in HP PCL, State 8 of the Wista 8 Fonts (Calibri, Cambria, Jadie Wista 8 Fonts (Calibri, Cambria); addit 8.0-in (20.3 cm) color LCD with touchscree	Supported: Yes; Fax Phone TAM Interface Supposed: Yes; Ti Supported: Y	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 200T network; 1 Foreign Interface; 1 Hardware Base-T; 802.3az (EEE) support on Fast Ethern 19 (optional) chase of a hardware accessory 33.6 kbps 68 D MHz 2000 pages 0 20,000 pages 0 20,0	receive only); Junk Barrier Supported: Yes; PC Inter hone Mode Supported: No Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirelet and Gig Links; 1912 mm); 803.88 (64-bit), Windows Server 2012 (64-bit); 1912 mm); 1912 mm; 1913 mm; 1914 mm; 1914 mm; 1915
Fax features Connectivity Standard connectivity Network capabilities Wireless capability Modern Memory Processor speed Output Recommonthly page volume? Paper handing Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the box* Warranty features Compatible operating systems Minimum system equirements Conts and Typefaces Control panel	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable Paper (color, letterhe Paper (color, letterhe 24.2 x 25.6 x 24 in (614 x 649 x 609 mm) Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm) 119.3 lb (54.11 kg) M725dn: HP Laser Jet Enterprise MFP M725; Windows 8, Windows 7, Windows Vista, Windo 10.6, 05 X Lion, 05 X Mountain Lion; For the lates hp.com/go/unixmodelscripts, hp.com/go/Jet. Windows 7, Windows Vista, Windows 7, Windows Vista, Windows 7, Windows Vista, Windows 7, Windows Vista, Windows 105 internal TrueType fonts scalable in HP PCL, State 8 of the Wista 8 Fonts (Calibri, Cambria, Jadie Wista 8 Fonts (Calibri, Cambria); addit 8.0-in (20.3 cm) color LCD with touchscree	Supported: Yes; Fax Phone TAM Interface Suppose Supported: Yes; Ti Supported: Yes; Tray 1: 16 to 53 lb (60 to 199 g/m²); Tray 1: 3 x 5 to 12.3 x 18.5 in; Tray 2: 5.8 x 8.3 to Supported: Yes; Tray 1: 3 x 5 to 12.3 x 18.5 in; Tray 2: 5.8 x 8.3 to Supported: Yes; Tray 1: 3 x 5 to 12.3 x 18.5 in; Tray 2: 5.8 x 8.3 to Supported: Yes; Yes; Yes; Yes; Yes; Yes; Yes; Yes;	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 200T network; 1 Foreign Interface; 1 Hardware Base-T; 802.3az (EEE) support on Fast Ethern 19 (optional) chase of a hardware accessory 33.6 kbps 68 D MHz 2000 pages 0 20,000 pages 0 20,0	receive only); Junk Barrier Supported: Yes; PC Interhone Mode Supported: No Integration Pocket; 2 Internal USB Host et and Gig Links; IPsec (standard); 802.11b/g/n wirele tet and Gig Links; 8
Fax features Connectivity Standard connectivity Network capabilities Wireless capability Modem Memory Processor speed Duty cycle (monthly, A4) ⁶ Recom monthly page volume ⁷ Paper handing Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the box ⁶ Warranty features Compatible operating systems Winimum system requirements Fonts and Typefaces Control panel Software included	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable Paper (color, letterhe Paper (color, letterhe 24.2 x 25.6 x 24 in (614 x 649 x 609 mm) Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm) 119.3 lb (54.11 kg) M725dn: HP Laser Jet Enterprise MFP M725; Windows 8, Windows 7, Windows Vista, Windo 10.6, 05 X Lion, 05 X Mountain Lion; For the lates hp.com/go/unixmodelscripts, hp.com/go/Jet. Windows 7, Windows Vista, Windows 7, Windows Vista, Windows 7, Windows Vista, Windows 7, Windows Vista, Windows 105 internal TrueType fonts scalable in HP PCL, State 8 of the Wista 8 Fonts (Calibri, Cambria, Jadie Wista 8 Fonts (Calibri, Cambria); addit 8.0-in (20.3 cm) color LCD with touchscree	Supported: Yes; Fax Phone TAM Interface Supposed: Yes; Ti Supported: Y	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi (2007 network; 1 Foreign Interface; 1 Hardware Base-T; 802.3az (EEE) support on Fast Ethern (9 (optional) chase of a hardware accessory 33.6 kbps (68 0 MHz),000 pages 0 20,000 pages 0 2	preceive only); Junk Barrier Supported: Yes; PC Interhone Mode Supported: No Integration Pocket; 2 Internal USB Host et and Gig Links; IPsec (standard); 802.11b/g/n wirele Integration Pocket; 2 Internal USB Host et and Gig Links; IPsec (standard); 802.11b/g/n wirele Integration Pocket; 2 Internal USB Host et and Gig Links; IPsec (standard); 802.11b/g/n wirele Integration Pocket; 2 Integration Pocket Integration Pocket; 2 Integration Pocket Integr
Fax features Connectivity Standard connectivity Network capabilities Wireless capability Modem Memory Processor speed Outy cycle (monthly, A4) ⁶ Recom monthly page volume ⁷ Paper handing Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the box ⁶ Warranty features Compatible operating systems Winimum system requirements Fonts and Typefaces Control panel Software included	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable Paper (color, letterhe Paper (color, letterhe 24.2 x 25.6 x 24 in (614 x 649 x 609 mm) Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm) 119.3 lb (54.11 kg) M725dn: HP Laser Jet Enterprise MFP M725; Windows 8, Windows 7, Windows Vista, Windo 10.6, 05 X Lion, 05 X Mountain Lion; For the lates hp.com/go/unixmodelscripts, hp.com/go/Jet. Windows 7, Windows Vista, Windows 7, Windows Vista, Windows 7, Windows Vista, Windows 7, Windows Vista, Windows 105 internal TrueType fonts scalable in HP PCL, State 8 of the Wista 8 Fonts (Calibri, Cambria, Jadie Wista 8 Fonts (Calibri, Cambria); addit 8.0-in (20.3 cm) color LCD with touchscree	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Ti Supported:	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 00T network; 1 Foreign Interface; 1 Hardware IBase-T; 802.3az (EEE) support on Fast Ethern go (potional) chase of a hardware accessory 33.6 kbps GB 0 MHz 0,000 pages 0 20,000 pages 0 20,000 pages 0 11,7 x 14.3 in; Trays 3-6: 5.8 x 8.3 to 11.7 x 100 sheets 29.3 x 26.8 x 4 Max: 36.1 x 40.6 x 206.3 lb (92.35 kg) lardware Installation Guide, Support flyer, Wal 1725z+: Same as above plus Telecom cablesite warranty Server 2008 (32 and 64-bit), Windows Server 20 cerminal Services (hp. com/go/sup/d); Novell (nove go/sap/frivers, hp.com/go/sap/frivin); HP e ows Server 2008, Windows Server 2008 R2, Ware system requirements, see microsoft.com; wstem compatible hardware system requirements unlation (Euro symbol built-in); 1 internal Unicemory cards; HP Laser/et Fonts and IPDS Em ome button (for quick return to the Home meiostscript emulation driver & Installer on Web], ure emissions bystander (active, printing): 5	receive only); Junk Barrier Supported: Yes; PC Interhone Mode Supported: No Integration Pocket; 2 Internal USB Host et and Gig Links; IPsec (standard); 802.11b/g/n wirele Integration Pocket; 2 Internal USB Host et and Gig Links; IPsec (standard); 802.11b/g/n wirele It is a support of the
Fax features Connectivity Standard connectivity Network capabilities Wireless capability Moder Memory Processor speed Outy cycle (monthly, A4) ⁵ Recom monthly page volume ⁷ Paper handing Media type Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the box ⁶ Warranty features Compatible operating systems Minimum system requirements Fonts and Typefaces Control panel Software included Invironmental ranges	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable Paper (color, letterhe 24.2 x 25.6 x 24 in (614 x 649 x 609 mm) Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm) 119.3 lb (54.11 kg) M725dn: HP Laser Jet Enterprise MFP M725; Windows 8, Windows 7, Windows Vista, Windon 10.6, 05 X Lion, 05 X Mountain Lion; For the later hp.com/go/junkmodelscripts, hp.com/go/j PC: Windows 8, Windows 7, Windows Vista, Windom 105 internal TrueType fonts scalable in HP PCL, Vista 8 Fonts (Calibri, Cambria); addit 8.0-in (20.3 cm) color LCD with touchscree Windows Instal	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Ti Supported:	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 00T network; 1 Foreign Interface; 1 Hardware IBase-T; 802.3az (EEE) support on Fast Ethern go (potional) chase of a hardware accessory 33.6 kbps GB 0 MHz 0,000 pages 0 20,000 pages 0 20,000 pages 0 11,7 x 14.3 in; Trays 3-6: 5.8 x 8.3 to 11.7 x 100 sheets 29.3 x 26.8 x 4 Max: 36.1 x 40.6 x 206.3 lb (92.35 kg) lardware Installation Guide, Support flyer, Wal 1725z+: Same as above plus Telecom cablesite warranty Server 2008 (32 and 64-bit), Windows Server 20 cerminal Services (hp. com/go/sup/d); Novell (nove go/sap/frivers, hp.com/go/sap/frivin); HP e ows Server 2008, Windows Server 2008 R2, Ware system requirements, see microsoft.com; wstem compatible hardware system requirements unlation (Euro symbol built-in); 1 internal Unicemory cards; HP Laser/et Fonts and IPDS Em ome button (for quick return to the Home meiostscript emulation driver & Installer on Web], ure emissions bystander (active, printing): 5	receive only); Junk Barrier Supported: Yes; PC Interhone Mode Supported: No Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele It is a links; IPsec (stan
Fax features connectivity Standard connectivity Network capabilities Wireless capability Modern Memory Processor speed Outry cycle (monthly, A4) ⁶ Netecom monthly page volume ⁹ Paper handing Media type Media type Media sizes ADF capacity Olimensions (W x D x H) Weight What's in the box ⁶ Varranty features compatible operating ystems Alinimum system equirements control panel ioftware included wirronmental ranges Operating humidity range:	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable Paper (color, letterhe 24.2 x 25.6 x 24 in (614 x 649 x 609 mm) Max: 34.1 x 38.9 x 24 in (855 x 989 x 609 mm) 119.3 lb (54.11 kg) M725dn: HP Laser Jet Enterprise MFP M725; Windows 8, Windows 7, Windows Vista, Windon 10.6, 0S X Lion, 0S X Mountain Lion; For the lates hp.com/go/unixmodelscripts, hp.com/go/J PC: Windows 8, Windows 7, Windows Vista, Windom Mac: Mac OS X 10.6, OS X Lion, OS X Mountain Lion; For the lates hp.com/go/unixmodelscripts, hp.com/go/J PC: Windows 8, Windows 7, Windows Vista, Windom State hp.com/go/unixmodelscripts, hp.com/go/J PC: Windows 8, Windows 7, Windows Vista, Windoms Internal TrueType fonts scalable in HP PCL, Vista 8 Fonts (Calibri, Cambria); addit 8.0-in (20.3 cm) color LCD with touchscree Windows Instal 20 to 80% RH e: 10 to 90% RH nicity range: 30 to 70% RH	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Ti Supported:	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi OOT network; 1 Foreign Interface; 1 Hardware IBase-T; 802.3az (EEE) support on Fast Ethern go (potional) chase of a hardware accessory 33.6 kbps GB O MHz 0.000 pages 0 20.000 pages 0 20.000 pages ough, tough paper), bond, cardstock, envelope Trays 2-6: 16 to 32 lb (60 to 120 g/m²) o 11.7 x 14.3 in; Trays 3-6: 5.8 x 8.3 to 11.7 x 100 sheets 29.3 x 26.8 x 4 Max: 36.1 x 40.6 x 206.3 lb (92.35 kg) Hardware Installation Guide, Support flyer, Wal 17-25*: Same as above plus Telecom cable 17-25*: Server 2008 (32 and 64-bit), Windows Server 20erminal Services (hp.com/go/upd); Novell (nove go/sap/drivers, hp.com/go/sap/drivin); HP eows Server 2008, Windows Server 2008 R2, ware system requirements, see microsoft.com system compatible hardware system requirementual unic nemory cards; HP Laser Jet Fonts and IPDS Em ome button (for quick return to the Home meiostscript emulation driver & Installer on Web], ure emissions bystander (active, printing): 5 ure emissions bystander (ready): 8 between the service of	preceive only); Junk Barrier Supported: Yes; PC Interhone Mode Supported: No Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wireli let and Gig Links;
Fax features Connectivity Standard connectivity Network capabilities Wireless capability Modem Memory Processor speed Outy cycle (monthly, A4) ⁶ Netecom monthly page volume ⁷ Paper handing Media type Media weight Custom media sizes ADF capacity Olimensions (W x D x H) Weight What's in the box ⁸ Warranty features Compatible operating systems Winimum system equirements Control panel Coftware included Coftware included Operating humidity range: Non-operating humidity range:	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable Paper (color, letterhe Paper (color, letterhe 24.2 x 25.6 x 24 in (614 x 649 x 609 mm) Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm) 119.3 lb (54.11 kg) M725dn: HP LaserJet Enterprise MFP M725; Windows 8, Windows 7, Windows Vista, Windo 10.6, 05 X Lion, 05 X Mountain Lion; For the lates hp.com/go/unixmodelscripts, hp.com/go/j PC: Windows 8, Windows 7, Windows Vista, Windo Mac: Mac OS X 10.6, 05 X Lion, 05 X Mount. 105 internal TrueType fonts scalable in HP PCL, 9 Vista 8 Fonts (Calibri, Cambria); addit 8.0-in (20.3 cm) color LCD with touchscree Windows Instal 20 to 80% RH e: 10 to 90% RH indity range: 30 to 70% RH	Supported: Yes; Fax Phone TAM Interface Supposed: Yes; Ti Supported: Y	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi (2007) network; 1 Foreign Interface; 1 Hardware Base-T; 802.3az (EEE) support on Fast Ethern (9 (optional)) chase of a hardware accessory 33.6 kbps GB 0 MHz 0,000 pages 0 20,000 pages 0 20,000 pages 0 20,000 pages 0 20,000 pages 0 11.7 x 14.3 in; Trays 3-6: 5.8 x 8.3 to 11.7 x 1,000 sheets 29.3 x 26.8 x 4 Max: 36.1 x 40.6 to 120 g/m²) 17252*: Same as above plus Telecom cable 1-site warranty Server 2008 (32 and 64-bit), Windows Server 20 erminal Services (hp.com/go/sap/drivers, hp.com/go/sap/print); HP e ows Server 2008 R2, where system requirements, see microsoft.com ystem compatible hardware system requirementy cards; HP Laser/let Fonts and IPDS Emomy cards; HP Laser/let Fonts and IPDS Emome button (for quick return to the Home me ostscript emulation driver & Installer on Web), sure emissions bystander (active, printing): 3 ype: equired: 1	preceive only); Junk Barrier Supported: Yes; PC Interhone Mode Supported: No Integration Pocket; 2 Internal USB Host et and Gig Links; IPsec (standard); 802.11b/g/n wirele Integration Pocket; 2 Internal USB Host et and Gig Links; IPsec (standard); 802.11b/g/n wirele It is a support of the support of th
Fax features connectivity Standard connectivity Network capabilities Wireless capability Modern Modern Memory Processor speed Outy cycle (monthly, A4)'s Recom monthly page volume' Paper handing Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the box's Warranty features Compatible operating Systems Minimum system equirements Control panel Coftware included Evironmental ranges Operating humidity range: Non-operating humidity range: Recommended operating hum Operating temperature range: Recommended operating tem Operating temperature range: Recommended operating tem	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable Paper (color, letterhe Paper (color, letterhe 24.2 x 25.6 x 24 in (614 x 649 x 609 mm) Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm) 119.3 lb (54.11 kg) M725dn: HP Laser Jet Enterprise MFP M725; Windows 8, Windows 7, Windows Vista, Window 10.6, OS X Lion, OS X Mountain Lion; For the lates hp.com/go/unixmodelscripts, hp.com/go/Jip PC: Windows 8, Windows 7, Windows Vista, Windows 10.5 internal TrueType fonts scalable in HP PCL, vista 8 Fonts (Calibri, Cambria); addite 8.0-in (20.3 cm) color LCD with touchscree Windows Instal 20 to 80% RH e: 10 to 90% RH nidity range: 30 to 70% RH : 50 to 91° F (10 to 32.5° C)	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Ti Supported:	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 00T network; 1 Foreign Interface; 1 Hardware IBase-T; 802.3az (EEE) support on Fast Ethern ig (optional) chase of a hardware accessory 33.6 kbps 6B 0 MHz 0,000 pages 0 20,000 pages ough, tough paper), bond, cardstock, envelope Trays 2-6: 16 to 32 lb (60 to 120 g/m²) 0 11,7 x 14.3 in; Trays 3-6: 5.8 x 8.3 to 11.7 x 100 sheets 29.3 x 26.8 x 4 Max: 36.1 x 40.6 x 206.3 lb (92.35 kg) lardware Installation Guide, Support flyer, Wa 17252+'s Same as above plus Telecom cable -site warranty Server 2008 (32 and 64-bit), Windows Server 20 terminal Services (hp.com/go/upd); Novell (nove/go/sap/drivers, hp.com/go/sap/print); HP e ows Server 2008, Windows Server 2008 R2, Ware system requirements, see microsoft.com: ystem compatible hardware system requirementulation (Euro symbol built-in); 1 internal Unic memory cards; HP Laser Jet Fonts and IPDS Em ome button (for quick return to the Memore mostscript emulation driver & Installer on Web], are emissions bystander (active, printing): 5 are emissions bystander (ready): ype: Bequired: 1	receive only); Junk Barrier Supported: Yes; PC Interhone Mode Supported: No Integration Pocket; 2 Internal USB Host et and Gig Links; IPsec (standard); 802.11b/g/n wirel et and Gig Links; 802.11b/g/n wirel et and Gig Links; 802.11b/g/n wirel et and Gig Links; 802.
Fax features connectivity Standard connectivity Network capabilities Wireless capability Modern Memory Processor speed Juty cycle (monthly, A4) ⁶ letcom monthly page volume ⁷ Paper handing Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the box ⁶ Warranty features compatible operating systems Alinimum system equirements control panel coftware included Invironmental ranges Operating humidity range: Non-operating humidity range: Non-operating humidity range: Non-operating humidity range: Recommended operating hum Operating temperature range: Recommended operating hum	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable Paper (color, letterhe Paper (color, letterhe 24.2 x 25.6 x 24 in (614 x 649 x 609 mm) Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm) 119.3 lb (54.11 kg) M725dn: HP LaserJet Enterprise MFP M725; Windows 8, Windows 7, Windows Vista, Windo 10.6, 05 X Lion, 05 X Mountain Lion; For the lates hp.com/go/unixmodelscripts, hp.com/go/j PC: Windows 8, Windows 7, Windows Vista, Windo Mac: Mac OS X 10.6, 05 X Lion, 05 X Mount. 105 internal TrueType fonts scalable in HP PCL, 9 Vista 8 Fonts (Calibri, Cambria); addit 8.0-in (20.3 cm) color LCD with touchscree Windows Instal 20 to 80% RH e: 10 to 90% RH indity range: 30 to 70% RH	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Ti Supported:	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 100T network; 1 Foreign Interface; 1 Hardware 18ase-T; 802.3az (EEE) support on Fast Ethern 19 (optional) 1 chase of a hardware accessory 33.6 kbps 6B 10 MHz 10,0000 pages 10,000 p	In receive only); Junk Barrier Supported: Yes; PC Interhone Mode Supported: No Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirel Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirel Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirel Integration Integration Integration Integration Integration Integration Integration Integration Integration Integration Integration Integration Integration Integration Integration Integration Integration Integration Integration Integration Integration Integration Integration Integration Integration Integration Integration Integration Integration Integration Integration Integration Integration Integration Integration Integration Integration Integration Integrat
Fax features Connectivity Standard connectivity Network capabilities Wireless capability Modem Memory Processor speed Outy cycle (monthly, A4) ⁶ Recom monthly page volume ⁷ Paper handing Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the box ⁸ Warranty features Compatible operating systems Winimum system requirements Fonts and Typefaces Control panel Software included Operating humidity range: Non-operating humidity range: Non-operating humidity range: Non-operating humidity range: Recommended operating hum Operating temperature range: Recommended operating tem Storage temperature range: Recommended operating tem Storage temperature range: Countrol panel Recommended operating hum Recommended operating hum Recommended operating hum Storage temperature range: Countrol range rang	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable Paper (color, letterhe Paper (color, letterhe 24.2 x 25.6 x 24 in (614 x 649 x 609 mm) Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm) 119.3 lb (54.11 kg) M725dn: HP LaserJet Enterprise MFP M725; Windows 8, Windows 7, Windows Vista, Window 10.6, 0S X Lion, 0S X Mountain Lion; For the lates hp. com/go/junixmodelscripts, hp. com/go/j PC: Windows 8, Windows 7, Windows Vista, Window 10.6, 0S X Lion, 0S X Lion, 0S X Mountain Lion; For the lates hp. com/go/junixmodelscripts, hp. com/go/j PC: Windows 8, Windows 7, Windows Vista, Window 10.6, 0S X Lion, 0S X Lion, 0S X Lion, 0S X Mountain Lion; For the lates hp. com/go/j PC: Windows 8, Windows 7, Windows Vista, Windows Internal TrueType fonts scalable in HP PCL, 9 Vista 8 Fonts (Calibri, Cambria); addit 8.0-in (20.3 cm) color LCD with touchscree Windows Install 20 to 80% RH e: 10 to 90% RH indity range: 30 to 70% RH e: 50 to 91° F (10 to 32.5° C) 32 to 140° F (0 to 60° C)	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Ti Supported:	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 200T network; 1 Foreign Interface; 1 Hardware Base-T; 802.3az (EEE) support on Fast Ethern 18 (potpional) chase of a hardware accessory 33.6 kbps 68 0 MHz 20,000 pages 0 2	in receive only); Junk Barrier Supported: Yes; PC Interhone Mode Supported: No Integration Pocket; 2 Internal USB Host et and Gig Links; IPsec (standard); 802.11b/g/n wirele Integration Pocket; 2 Internal USB Host et and Gig Links; IPsec (standard); 802.11b/g/n wirele It is a considerable of the secondard of
Fax features Connectivity Standard connectivity Network capabilities Wireless capability Modem Memory Processor speed Outy cycle (monthly, A4) ⁵ Recom monthly page volume ⁷ Paper handing Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the box ⁸ Warranty features Compatible operating systems Minimum system requirements Fonts and Typefaces Control panel Coftware included Invironmental ranges Operating humidity range: Non-operating humidity range Recommended operating hum Operating temperature range: Coustic Tower emissions: Manage temperature range: Coustic Tower emissions:	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable Paper (color, letterhe Paper (color, letterhe Paper (color, letterhe 24.2 x 25.6 x 24 in (614 x 649 x 609 mm) Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm) 119.3 lb (54.11 kg) M725dn: HP Laser Jet Enterprise MFP M725; Windows 8, Windows 7, Windows Vista, Windon 10.6, OS X Lion, OS X Mountain Lion; For the lates hp.com/go/unixmodelscripts, hp.com/go/j PC: Windows 8, Windows 7, Windows Vista, Windoms Vista, Windoms 10.6, OS X Lion, OS X Mountain Lion; For the lates hp.com/go/inixmodelscripts, hp.com/go/j PC: Windows 8, Windows 7, Windows Vista, Windoms Vista, Windoms Vista, Windoms Instal 10.5 internal TrueType fonts scalable in HP PCL, Vista 8 Fonts (Calibri, Cambria); addit 8.0-in (20.3 cm) color LCD with touchscree Windows Instal 20 to 80% RH e: 10 to 90% RH nidity range: 30 to 70% RH FOR 10 to 32.5° C) 32 to 140° F (0 to 60° C) 6.8 B(A)	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Ti Supported:	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 00T network; 1 Foreign Interface; 1 Hardware IBase-T; 802.3az (EEE) support on Fast Ethern go (potional) chase of a hardware accessory 33.6 kbps GB 0 MHz 0,000 pages 0 20,000 pages 0 20,000 pages 0 11.7 x 14.3 in; Trays 3-6: 5.8 x 8.3 to 11.7 x 100 sheets 29.3 x 26.8 x 4 Max: 36.1 x 40.6 x 206.3 lb (92.35 kg) lardware Installation Guide, Support flyer, Wa ITZ52+', Same as above plus Telecom cable -site warranty Server 2008 (32 and 64-bit), Windows Server 20erminal Services (ipp.com/go/upd); Novell (nover go/sap/drivers, hp.com/go/sap/print); HP e ows Server 2008 (Windows Server 2008 R2, Warren Compatible hardware system requirement, see microsoft.com ystem compatible hardware system requirementulation (Euro symbol built-in); 1 internal Unic memory cards; HP LaserJet Fonts and IPDS Em tome button (for quick return to the Home metostscript emulation driver & Installer on Web] ure emissions bystander (active, printing): 5 are emissions bystander (ready): ype: equired:	receive only); Junk Barrier Supported: Yes; PC Interhone Mode Supported: No Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integration In
Fax features Connectivity Standard connectivity Network capabilities Wireless capability Modem Memory Processor speed Duty cycle (monthly, A4) ⁶ Recom monthly page volume ⁷ Paper handing Media type Media weight Custom media sizes ADF capacity Dimensions (W x D x H) Weight What's in the box ^a Warranty features Compatible operating systems Minimum system requirements Fonts and Typefaces Control panel Software included novironmental ranges Operating humidity range: Non-operating humidity range: Recommended operating hum operating temperature range: Recommended operating tem Storage temperature range: Coustic ^a	Not Applicable 2 Hi-Speed USB 2.0 Host; 1 Hi-S Via HP Jetdirect Ethernet embedded print serve Not Applicable Paper (color, letterhe 24.2 x 25.6 x 24 in (614 x 649 x 609 mm) Max: 34.1 x 38.9 x 24 in (865 x 989 x 609 mm) 119.3 lb (54.11 kg) M725dn: HP Laser Jet Enterprise MFP M725; Windows 8, Windows 7, Windows Vista, Windon 10.6, 0S X Lion, 0S X Mountain Lion; For the later hp.com/go/unixmodelscripts, hp.com/go/J PC: Windows 8, Windows 7, Windows Vista, Windoms Vista Windows 7, Windows Vista Windows 10.5 in Color of the later hp.com/go/unixmodelscripts, hp.com/go/J PC: Windows 8, Windows 7, Windows Vista, Windoms Vista Windows Nos X 10.6, 0S X Lion, 0S X Mountain Lion; For the later hp.com/go/J PC: Windows 8, Windows 7, Windows Vista, Windows 10.6, 0S X Lion, 0S X Mountain Lion; For the later hp.com/go/J Windows 8, Windows 7, Windows Vista, Windows 10.6, 0S X Lion, 0S X Mountain Lion; For the later hp.com/go/J Windows 8, Windows 7, Windows Vista, Windows 10.6, 0S X Lion, 0S X Mountain Lion; For the later hp.com/go/J PC: Windows 8, Windows 7, Windows Vista, Windows 10.6, 0S X Lion, 0S X Mountain Lion; For the later hp.com/go/J Windows 10.5 Mindows 10.5 Mindows Vista, Windows 10.6, 0S X Lion, 0S X Mountain Lion; For the later hp.com/go/J Windows 10.5 Mindows	Supported: Yes; Fax Phone TAM Interface Supported: Yes; Ti Supported:	orted: No; Fax Polling Supported: Yes (poll to elephone Handset Supported: No; Fax Telepi 100T network; 1 Foreign Interface; 1 Hardware 18ase-T; 802.3az (EEE) support on Fast Ethern g (optional) 1: chase of a hardware accessory 33.6 kbps 6B 10 MHz 10,000 pages 10 20,000 pages 10 20,000 pages 10 20,000 pages 10 20,000 pages 10 1.7 x 14.3 in; Trays 3-6: 5.8 x 8.3 to 11.7 x 100 sheets 10 20.3 to 11.7 x 14.3 in; Trays 3-6: 5.8 x 8.3 to 11.7 x 100 sheets 10 20.3 to 10 (92.35 kg) 1-4 radware Installation Guide, Support flyer, Wa 1725z±: Same as above plus Telecom cable 1-5site warranty 10 Server 2008, Windows Server 2008 R2, Ware system requirements, see microsoft.com; yestem compatible hardware system requirements, see microsoft.com; yestem compatible hardware system requirements untation (Euro symbol built-in); 1 internal Unic memory cards; HP Laser Jet Fonts and IPDS Em tome button (for qualton free Restricts) are emissions bystander (active, printing): 5 are emissions bystander (active, printing): 5 are emissions bystander (ready): 10 10 10 10 10 10 10 10 10 10 10 10 10 1	in receive only); Junk Barrier Supported: Yes; PC Interinone Mode Supported: No Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integration Pocket; 2 Internal USB Host let and Gig Links; IPsec (standard); 802.11b/g/n wirele Integration Pocket 10 Integration 10 Integr

Measured using ISO/IEC 24734, excludes first set of test documents. For more information see <a href="https://documents.peed-universal-u















